



LIFE BUOY / LIFE RING

Application

- 2.5kgs life buoy is suitable for all kinds of vessels, used by seamen and passengers for life-saving equipment.
- 4.3kgs life buoy is used to release the self-activated smoke signal, supplying life ring for the rescuees and research direction for the rescuers.

Standard: SOLAS 1974/1996, International Life-saving Appliance Code and MSC.81(70).

Material: outside HDPE, inside rigid polyurethane foam

Max. Drop Height: 80m

Approval Certificate: CCS EC



Type	IMPA code	Weight	Buoyancy	Outer Dia.	Inner Dia.	Thickness
5555-I	330151	2.5kgs	≥ 142N	720mm	440-450mm	105mm
5555-II	330151	4.3kgs	≥ 142N	720mm	440-450mm	105mm

LIFEBUOY SELF-IGNITION LIGHT



Type: RSQD-1

Flare time: ≥ 2hours

Luminous intensity: ≥ 2.0 cd

Flash frequency: 50-70times/min

Battery: Lithium Battery

Approval: CCS/EC



Type: RSQD-2

Flare time: ≥ 2hours

Luminous intensity: ≥ 2.0 cd

Flash frequency: 50-70times/min

Battery: Dry Battery

Approval: CCS/EC



lifebuoy rack

- ◆Material: Carbon steel

Lifebuoy floating lifeline

- ◆Diameter: 8mm
- ◆Length: $\geq 30m$
- ◆Material: Polypropylene
- ◆It can be equipped with floated shell



Lifebuoy quick release device

- ◆ Material: Fiber Reinforce Plastic
- ◆ One set contain two pieces, each board include one.



Horseshoe lifebuoy

- ◆ The outer diameter: 520mm
The inside diameter: 250mm
Thickness: 100mm
- ◆ Surface material: artificial leather
- ◆ Buoyancy material: EPE
- ◆ Available Colors: Orange/ Yellow/ White/ Red

