

CQYB/II-150N



SOLAS INFLATABLE LIFE JACKET

Technical Parameters

- **Standard:** SOLAS/MED
- **Certificate:** RINA, CCS
- **Air Chamber:** Double
- **Twin 33g CO₂ Cylinders**
- **Inflation:** Manual & Automatic
- **Fabric:** 400D Oxford + 0.15mm TPU
- **Buoyancy:** ≥ 150N
- **Weight:** ≤ 1.5kgs
- **Size:** Adult Universal
- **Angle in water face plane angle** ≥ 40°
- **Trunk angle** ≥ 30°
- **Ambient temperature:** -30-65°C
- **Freeboard** ≥ 12mm
- **Buoyancy Loss:** ≤ 5% in 24 hours
- **Inflation Time:** ≤ 5S
- **Floating Duration:** ≥ 48h
- **Accessories:** Whistle, Reflective Tape, CO₂ Cylinders, Manual & Automatic Inflation Systems, Life Jacket Light.
- **Application:** Marine Shipboard, Offshore Oil platform.





CQYB/I-275N



SOLAS INFLATABLE LIFE JACKET

Technical Parameters

- **Standard:** SOLAS/MED
- **Certificate:** RINA
- **Air Chamber:** Double
- **Twin 55g CO₂ Cylinders**
- **Inflation:** Manual & Automatic
- **Fabric:** 400D Oxford + 0.15mm TPU
- **Buoyancy:** ≥ 275N
- **Weight:** ≤ 1.5kgs
- **Size:** Adult Universal
- **Angle in water face plane angle** ≥40°
- **Trunk angle** ≥30°
- **Ambient temperature:** -30-65°C
- **Freeboard** ≥12mm
- **Buoyancy Loss:** ≤ 5% in 24 hours
- **Inflation Time:** ≤ 5S
- **Floating Duration:** ≥ 48h
- **Accessories:** Double Crotch Strap, Whistle, CO₂ Cylinders, Manual & Auto Inflation Device, Reflective Tape, Light.
- **Application:** Marine Shipboard, Offshore Oil platform.



CQYB/III-150N



INFLATABLE LIFE JACKET

Technical Parameters

- **Standard:** ISO 12402-3:2006
- **Air Chamber:** Single
- **Inflation:** Automatic Only
- **Buoyancy:** $\geq 150N$
- **Weight:** $\leq 1KG$
- **Size:** Adult Universal
- **Material:** PU Coated Fabric
- **Inflation Time:** $\leq 5S$
- **Floating Duration:** $\geq 48h$
- **Buoyancy Loss:** $\leq 5\%$ in 24 hours
- **Accessories:** Whistle, Reflective Tape, Oral Blow Tube, 33g CO₂ Cylinder, Automatic Inflation System.
- **Application:** Marine Work, Shipboard.

